



PE TROUGHS FOR KTC / IBC STORAGE

For the storage of aggressive media

- ✎ Rotation-moulded trough body made of black UV-stable PE / no welding seams
- ✎ Continuous reinforcement ribs ensure high load values
- ✎ Floor clearance for in-house transport
- ✎ Galvanized or PE support grids
- ✎ Corner openings for easily removable grids

Collection trough systems

Shelving systems for hazardous substances

Safety cabinets

Open-air storage systems / projects

Fire protection container systems

Gas cylinder storage systems

Safety containers, handling systems, ...



PE-KT-EP2, with optional PE drum stand, Art. No. P70-7103-A



PE-KT-EP1, Article No. P70-7100-A



General
Constructional
approval DIBt Berlin
Z-40.22-360



PE-KT-EP3, Article No. P70-7105-A



PE-KT-EP3, with optional PE drum stand, Article No. P70-7105-A

Model	PE-KT-EP1	PE-KT-EP2	PE-KT-EP3
External dimensions W x D x H mm	1290 x 1290 x 900	1720 x 1450 x 600	2490 x 1290 x 480
Collection volume, L	1000	1000	1000
Capacity, KTC / IBC	1	1	2
Article No., with galvanized grid	P70-7100-A	P70-7102-A	P70-7104-A
Article No., with PE grid	P70-7101-A	P70-7103-A	P70-7105-A

Accessory	Article No.
PE drum stand, provides extra height for filling processes, W x D x H mm = 1210 x 1200 x 400	P70-7110-A





PE KTC STATIONS

For the storage of aggressive media indoors and outdoors

PE trough construction:

- ✎ Rotation-moulded trough body made of black UV-stable PE / no welding seams
- ✎ Continuous reinforcement ribs ensure high load values
- ✎ Floor clearance for in-house transport
- ✎ Galvanised or PE support grids
- ✎ Corner openings for easily removable grids
- ✎ PE collection trough with general constructional approval from DIBt Berlin

Weather protection construction:

- ✎ Stable aluminium tube construction, held in position by footplates beneath the grid
- ✎ Polyester cover with roll-up front panel
- ✎ Supplied dismantled for easy on-site assembly



PE-KTC 1, Article No. P70-7121-A



PE-KTC 2, Article No. P70-7123-A



General
Constructional
approval DIBt Berlin
for collection troughs
Z-40.22-360



Both models also
suitable for storing
200 L drums!

- Collection trough systems
- Shelving systems for hazardous substances
- Safety cabinets
- Open-air storage systems / projects
- Fire protection container systems
- Gas cylinder storage systems
- Safety containers, handling systems, ...

Model	PE-KTC 1	PE-KTC 2
External dimensions of trough W x D x H mm	1290 x 1290 x 900	2490 x 1290 x 480
Collection volume, L	1000	1000
Capacity, 200 L drums	4	8
Capacity, KTCs / IBCs	1	2
External dimensions complete with weather protection W x D x H mm	1290 x 1290 x 2500	2490 x 1290 x 2080
Article No., with galvanized grid	P70-7120-A	P70-7122-A
Article No., with PE grid	P70-7121-A	P70-7123-A