



BSC - CLASSIC

- Fire protection container with fire resistance >90 minutes
- With fire chamber test
- Suitable for indoor and outdoor use**
- Steel collection trough as per WHG complete with grid cover
- Door hold-open device
- Doors close automatically if fire occurs
- Lifting attachments for cranes (for empty transport only)
- Lacquered exterior RAL 7038
- Lacquered interior RAL 9001
- Wide range of accessories



See practical info on pages 60 and 94!

**applied for General
Constructional Approval
DIBt Berlin**

**BSC1-CL, Article No. C64-2007-A,
for storing of 4 x 200 L drums
or 1 x 1000 L container**



Model	BSC 1-CL	BSC 2-CL	BSC 3-CL	BSC 4-CL	BSC 5-CL	BSC 6-CL	BSC 7-CL	BSC 8-CL
External dimensions W x D x H mm	1700 x 1700 x 2400	2000 x 2350 x 2400	3000 x 2350 x 2400	4000 x 2350 x 2400	5000 x 2350 x 2400	6000 x 2350 x 2400	7000 x 2350 x 2400	8000 x 2350 x 2400
Internal dimensions W x D x H mm	1460 x 1460 x 1750	1760 x 2100 x 2070	2760 x 2100 x 2070	3760 x 2100 x 2070	4760 x 2100 x 2070	5760 x 2100 x 2070	6760 x 2100 x 2070	7760 x 2100 x 2070
Collection volume, L	1000	500	800	1100	1500	1800	2100	2400
Net weight kg	1000	1500	2100	2550	2950	3400	3900	4400
Art. No. door W x H 1300 x 2000 mm (1D)*	C64-2007-A	C64-2000-A	C64-2001-A	C64-2002-A	C64-2003-A	C64-2004-A	C64-2005-A	C64-2006-A
Art. No. door W x H 2600 x 2000 mm (2D)** in longer side	-	-	C64-2031-A	C64-2032-A	C64-2033-A	C64-2034-A	C64-2035-A	C64-2036-A



BSC4-CL, Art. No. C64-2002-A, with optional grid-type shelf for small containers



FIRE BEHAVIOUR

- If a fire occurs the door(s) close automatically by Thermolock and door closing device**
- Doors, door gaps, air inlet/outlet openings are sealed hermetically**
- In versions with Thermolock system the doors can be left open during the work process**

* 1D = single door

** 2D = double door

Accessories	Article No.
Additional single door W x H in mm = 1300 x 1900	C64-2071-A
Ex-proof forced ventilation	C64-2090-A
Ex-proof illumination unit, 2 x 36 W	C64-2091-A
Ex-proof heating, 1000 W	C61-2092-A
Ex-proof heating, 2000 W	C61-2093-A
Ex-proof socket 230 V / 16 A	C61-2094-A
Shelf for small containers, basic unit with 4 grid-type storage levels, 600 mm deep, 1060 mm long	C64-2080-A
Shelf for small containers, extension unit with 4 grid-type storage levels, 600 mm deep, 1010 mm long	C64-2081-A
Additional grid-type storage level 1000	C64-2082-A
Shelf for small containers, basic unit with 4 grid-type storage levels, 600 mm deep, 1360 mm long	C64-2085-A
Shelf for small containers, extension unit with 4 grid-type storage levels, 600 mm deep, 1310 mm long	C64-2086-A
Additional grid-type storage level 1300	C64-2087-A
Drive-on ramp W x L mm = 1200 x 1200 for drum carts	C64-2083-A
Drive-on ramp W x L mm = 1200 x 1600 for pallet trucks	C64-2084-A

Collection
trough systems

Shelving systems for
hazardous substances

Safety
cabinets

Open-air storage
systems / projects

Fire protection
container systems

Gas cylinder
storage systems

Safety containers,
handling systems, ...