

BSC - FT WITH DOUBLE DOORS

Series PL is particularly suitable for storing goods on Euro or chemical pallets. The Thermolock system allows the doors to be left open during the work process. This means that the BSC can be used by one person without any problems.

Execution:

- ✎ Fire protection container with fire resistance >90 minutes
- ✎ With fire chamber test
- ✎ **Suitable for indoor and outdoor use**
- ✎ Steel collection trough as per WHG complete with grid cover
- ✎ Door hold-open device
- ✎ Doors close automatically if fire occurs
- ✎ Lacquered exterior RAL 7038
- ✎ Lacquered interior RAL 9001



See practical info on pages 60 and 94!

FIRE BEHAVIOUR

- If a fire occurs the door(s) close automatically by Thermolock and door closing device
- Doors, door gaps, air inlet/outlet openings are sealed hermetically
- In versions with Thermolock system the doors can be left open during the work process



BSC-2.30-FT, Article No. C64-2013-A



BSC-2.60-FT, Article No. C64-2011-A

applied for General
Constructional Approval
DIBt Berlin



Accessories such as forced ventilation, heating, illumination and shelving can be found on page 133!

Model	BSC-2.30-FT	BSC-2.60-FT	BSC-2.60-KTC-FT
External dimensions W x D x H mm	3000 x 1750 x 3000	6000 x 1750 x 3000	6000 x 1750 x 3450
Compartment dimensions W x D x H* mm	2600 x 1500 x 1250	2600 x 1500 x 1250	2600 x 1500 x 1500
Number of storage levels	2	2	2
Collection volume, L	800	1700	1700
Capacity, 200 L drums on Euro / chemical pallets	12 / 16	24 / 32	24 / 32
Capacity, KTCs/IBCs	-	-	8
Net weight kg	1900	3700	4000
Number of double doors	1	2	2
Article No.	C64-2013-A	C64-2011-A	C64-2015-A

* Compartment sizes and given capacities do not take electrical fittings (ventilation, lighting, etc.) into account