



ROOF, SIDES AND REAR WALLS IN F90 EXECUTION

- For storage of pressurized gas cylinders in accordance with the Technical Rules for Pressurized Gases, TRG 280
- Suitable for the storage of gas cylinders and cylinder pallets
- Fire resistant roof and walls as per DIN 4102
- Cantilever arm compartment divider with safety chains
- Internal and external walls lacquered (RAL 9001 inner, RAL 7038 outer)
- Delivered fully assembled
- Easy installation
- With projecting roof for weather protection
- Fire galvanized grid-type door(s) with safety lock
- Hinged or double door, depending on version



GFL-F90-10, Article No. C66-1010-A



Our standard: complete with base group!

GFL-F90-30, Article No. C66-1004-A, with optional separating wall



GFL-F90-20, Article No. C66-1002-A, with optional shelf

Can be set up directly against buildings without observing safety distances.

Model	GFL-F90-10	GFL-F90-15	GFL-F90-20	GFL-F90-25	GFL-F90-30
External dimensions W x D x H mm without projecting roof	1000 x 1150 x 2400	1500 x 1150 x 2400	2000 x 1150 x 2400	2500 x 1150 x 2400	3000 x 1150 x 2400
Internal dimensions W x D x H mm	760 x 1000 x 2200	1260 x 1000 x 2200	1760 x 1000 x 2200	2260 x 1000 x 2200	2760 x 1000 x 2200
Capacity: Cylinder pallets 1000 x 1200 mm Cylinders 230 mm dia.	- 9	1 or 15	1 or 21	1 pallet + 12 cylinders or 27	2 pallets or 1 pallet + 20 cylinders or 33
Net weight kg	300	500	700	1200	1700
Article No., without cylinder holders	C66-1000-A	C66-1001-A	C66-1002-A	C66-1003-A	C66-1004-A
Article No., with cylinder holders	C66-1010-A	C66-1011-A	C66-1012-A	C66-1013-A	C66-1014-A

Accessories	Article No.
Galvanized drive-in ramp	C66-1020-A
Separating wall (for GFL-F90-20 to GFL-F90-30 only)	C66-1021-A

Collection trough systems

Shelving systems for hazardous substances

Safety cabinets

Open-air storage systems / projects

Fire protection container systems

Gas cylinder storage systems

Safety containers, handling systems, ...