

For the storage of hazardous substances as barrelled goods on Euro or chemical pallets on 2 storage levels

By the combination of pallet racks with quality marks and rack base troughs in accordance with the Water Management Act (WHG) it is possible to obtain a flexible and favourably-priced storage system that can be extended at any time.

Pallet rack fittings:

- „Quality mark RAL-RG 614/2 Pallet racks“
- Ready-mounted support frames ---> short assembly time**
- Storage levels height-adjustable at intervals of 75 mm
- Galvanized support frames, powder-coated crossbeams, RAL 7035 light grey



See practical info on pages 60 and 94!

Rack base trough fittings:

- Ü-mark as per steel trough guidelines
- Made from 3 mm steel sheet
- Corrosion-protected by lacquering in RAL 5015 or **fire galvanizing**
- Floor clearance 100 mm



G-PR 2.27/360, basic and extension units



G-PR 2.22/360, basic and extension units



Bauregelleiste A Teil 1
DIBt Berlin



G-PR 2.27/360, basic unit



By the additional use of support grids it is also possible to store containers „without a pallet“ !

Model	G-PR 2.18/360	G-PR 2.22/360	G-PR 2.27/360
Rack dimensions W x D x H mm	1980 x 1100 x 2475	2380 x 1100 x 2475	2880 x 1100 x 2475
Inner width of unit mm	1800	2200	2700
Storage levels	2	2	2
Capacity, 200 L drums on Euro pallets	8	8	12
Capacity, 200 L drums on chemical pallets	8	8	16
Max. load kg	2600	2200	2700
Collection trough dimensions W x D x H mm	1780 x 1300 x 315	2180 x 1300 x 285	2680 x 1300 x 265
Collection volume, L	360	360	360
Article No., basic unit, trough lacquered RAL 5015	R23-3520-B	R23-3522-B	R23-3524-B
Article No., extension unit, trough lacquered RAL 5015	R23-3521-B	R23-3523-B	R23-3525-B
Article No., basic unit, trough fire galvanizing	R23-3510-B	R23-3512-B	R23-3514-B
Article No., extension unit, trough fire galvanizing	R23-3511-B	R23-3513-B	R23-3515-B


Accessories	Article No.	Article No.	Article No.
Push-through prevention safety device for 1 storage level	R23-3120-B	R23-3121-B	R23-3122-B
Support grid 1000 kg/m ²	R23-3100-B	R23-3101-B	R23-3102-B
Collision protection corner	R23-3110-B	R23-3110-B	R23-3110-B



For the storage of hazardous substances as barrelled goods on Euro or chemical pallets on 3 storage levels



G-PR 3.22/360, basic unit



Bauregelliste A Teil 1
DIBt Berlin



See practical info
on pages 60 and 94!



G-PR 3.27/660, basic unit



By the additional use of support grids it is also possible to store containers „without a pallet“ !



Combining different unit widths allows the optimal utilisation of storage space!



KTC racks with collection troughs for hazardous substances can be found on page 58!

Model	G-PR 3.18/360	G-PR 3.22/360	G-PR 3.27/660
Rack dimensions W x D x H mm	1980 x 1100 x 3600	2380 x 1100 x 3600	2880 x 1100 x 3600
Inner width of unit mm	1800	2200	2700
Storage levels	3	3	3
Capacity, 200 L drums on Euro pallets	12	12	18
Capacity, 200 L drums on chemical pallets	12	12	24
Max. load kg	2600	2200	2700
Collection trough dimensions W x D x H mm	1780 x 1300 x 315	2180 x 1300 x 285	2680 x 1300 x 355
Collection volume, L	360	360	660
Article No., basic unit, trough lacquered RAL 5015	R23-3526-B	R23-3528-B	R23-3530-B
Article No., extension unit, trough lacquered RAL 5015	R23-3527-B	R23-3529-B	R23-3531-B
Article No., basic unit, trough <u>fire galvanized</u>	R23-3516-B	R23-3518-B	R23-3508-B
Article No., extension unit, trough <u>fire galvanized</u>	R23-3517-B	R23-3519-B	R23-3509-B

Accessories	Article No.	Article No.	Article No.
Push-through prevention safety device for 1 storage level	R23-3120-B	R23-3121-B	R23-3122-B
Support grid 1000 kg/m ²	R23-3100-B	R23-3101-B	R23-3102-B
Collision protection corner	R23-3110-B	R23-3110-B	R23-3110-B

Collection trough systems

Shelving systems for hazardous substances

Safety cabinets

Open-air storage systems / projects

Fire protection container systems

Gas cylinder storage systems

Safety containers, handling systems, ...

For the storage of KTCs / IBCs or large containers

Pallet rack fittings:

- „Quality mark RAL-RG 614/2 Pallet racks“
- Ready-mounted support frames ---> short assembly time**
- Storage levels height-adjustable at intervals of 75 mm
- Galvanized support frames, powder-coated crossbeams, RAL 7035 light grey

Rack base trough fittings:

- Ü-mark as per steel trough guidelines
- Made from 3 mm sheet steel
- Corrosion-protected by lacquering in RAL 5015 or **fire galvanizing**
- Floor clearance 100 mm
- Collection volume 1000 L
- For models with 3 storage levels the collection trough is equipped with a support grid for use as the first storage level.



See practical info on pages 60 and 94!




G-KR 3.27/1000, basic unit



By the additional use of support grids it is also possible to store various KTCs and large containers!



G-KR 2.22/1000, basic unit



Other versions available on request !



G-KR 2.27/1000, basic unit

Model	G-KR 2.22/1000	G-KR 2.27/1000	G-KR 3.22/1000	G-KR 3.27/1000
Rack dimensions W x D x H mm	2380 x 1100 x 3000	2880 x 1100 x 3000	2380 x 1100 x 4725	2880 x 1100 x 4725
Inner width of unit mm	2200	2700	2200	2700
Storage levels	2	2	3	3
Capacity, KTC / IBC	4	4	6	6
Max. load kg	3000	4000	3000	4000
Collection trough dimensions W x D x H mm	2180 x 1300 x 535	2680 x 1300 x 455	2180 x 1300 x 565	2680 x 1300 x 485
Collection volume, L	1000	1000	1000	1000
Article No., basic unit, trough lacquered RAL 5015	R23-3620-B	R23-3622-B	R23-3624-B	R23-3626-B
Article No., extension unit, trough lacquered RAL 5015	R23-3621-B	R23-3623-B	R23-3625-B	R23-3627-B
Article No., basic unit, trough <u>fire galvanizing</u>	R23-3610-B	R23-3612-B	R23-3614-B	R23-3616-B
Article No., extension unit, trough <u>fire galvanizing</u>	R23-3611-B	R23-3613-B	R23-3615-B	R23-3617-B

Accessories	Article No.	Article No.	Article No.	Article No.
Push-through prevention safety device for 1 storage level	R23-3121-B	R23-3122-B	R23-3121-B	R23-3122-B
Support grid 1500 kg/m ²	R23-3106-B	R23-3107-B	R23-3106-B	R23-3107-B
Collision protection corner	R23-3110-B	R23-3110-B	R23-3110-B	R23-3110-B