

Approved for storage of pressurized gas cylinders at the workplace as per EN 14470-2 (G 30)

- ✎ Whole construction tested and approved by recognized materials testing institute as per EN 14470-2
- ✎ GS-approved safety
- ✎ Insulation according to DIN 4102
- ✎ Outer body powder-coated steel sheet in RAL 7035 - light grey, door/s either in RAL 7035 - light grey or RAL 1007 - daffodil yellow
- ✎ Inner body made of HPL-coated sheets - RAL 7035 - light grey
- ✎ Stainless steel base plate
- ✎ Automatic thermal closing mechanism if fire occurs: inlet and outlet channels after temperature increase to 70°C (±10°C)
- ✎ DN 75 ventilation connection for exhaust air extraction
- ✎ Levelling feet for installing cabinet horizontally
- ✎ Door/s with cylinder lock
- ✎ **With inner fittings:**
 - 1 x stainless steel floor plate
 - 1 x holder for 50-litre gas cylinder per cylinder place
 - 2 x horizontal C-rails for attaching gas fittings



SiZ G30/1200, Art.-No. B80-5017-C, with side-mounted shelf, optional



**Extraction fans
please see
page 54 !**



SiZ G30/600, Art.-No. B80-5015-C

Model	SiZ G30/600	SiZ G30/900	SiZ G30/1200	SiZ G30/1400
External dimensions W x D x H in mm	595 x 598 x 2015	900 x 598 x 2015	1190 x 598 x 2015	1400 x 598 x 2015
Intern. dim. W x D x H in mm	492 x 430 x 1785	797 x 430 x 1785	1087 x 430 x 1785	1297 x 430 x 1785
Capacity	up to two (2) 50 l gas cylinders	up to three (3) 50 l gas cylinders	up to four (4) 50 l gas cylinders	up to four (4) 50 l gas cylinders
Door/s	1 (DIN right)	2	2	2
Weight (kg)	295	375	475	610
Outer body: RAL 7035 – light grey				
Art.-No., door/s: RAL 7035 - light grey	B80-5015-C	B80-5016-C	B80-5017-C	B80-5018-C
Art.-No., door/s: RAL 1007 - daffodil yellow	B80-5015-G	B80-5016-G	B80-5017-G	B80-5018-G

Accessories				
Shelf*	B80-5010-C	B80-5011-C	B80-5012-C	B80-5013-C
Side-mounted shelf	suitable for all models			B80-5014-C
Drive-in ramp, stainless steel V2A	suitable for all models			B80-2833-A

*) Shelf across whole width of safety cabinet, powder-coated steel sheet in RAL 7035 - light grey.