



Collection trough systems

Shelving systems for hazardous substances

Safety cabinets

Open-air storage systems / projects

Fire protection container systems

Gas cylinder storage systems

Safety containers, handling systems, ...

For storing hazardous substances frost-free or at constant temperature

- Supplied ready-assembled
- Safety storehouse insulation: insides of all walls, roof and doors fitted with 60 mm thick, non-flammable insulation material
- Insulation of collection trough optional
- Heating depends on size and required interior temperature
- Continuous liquid channels, except in door area
- With grounding connection to avoid dangerous electrostatic charges (for Ex-zone 2)
- For the storage of class A1 to AIII and B hazardous substances a forced ventilation system is required.

Our standard: double-door and lifting attachments for cranes!



Thermo safety storehouse SLT 3 x 2, galvanized, with special fittings



See practical info on pages 60 and 94!



Our standard: double-door and lifting attachments for cranes!



Thermo safety storehouse SLT 4 x 3, galvanized, with additional collection trough insulation



Double door in longer side as standard, doors in shorter side on request!



General Constructional approval DIBt Berlin Z-38.5-171



Equipped with shelving for use as small container storehouse



Equipped with shelving for use as small container storehouse



Our standard: double-door and lifting attachments for cranes!



General
Constructional
approval DIBt Berlin
Z-38.5-171



Collection
trough systems

Shelving systems for
hazardous substances

Safety
cabinets

Open-air storage
systems / projects

Fire protection
container systems

Gas cylinder
storage systems

Safety containers,
handling systems, ...

Thermo safety storehouse SLT 5 x 2, galvanized and outside lacquered, with optional fittings

Type 2						
Model	SLT 1 x 2	SLT 2 x 2	SLT 3 x 2	SLT 4 x 2	SLT 5 x 2	SLT 6 x 2
Dimensions L x W mm	1075 x 2075	2075 x 2075	3075 x 2075	4075 x 2075	5075 x 2075	6075 x 2075
Total height mm	2375	2375	2375	2375	2375	2375
Collection volume, L	300	660	1000	1000	1000	1000
Art. No., galvanized	H63-1000-A	H63-1001-A	H63-1002-A	H63-1003-A	H63-1004-A	H63-1005-A
Art. No., galvanized, outside lacquered	H63-2000-A	H63-2001-A	H63-2002-A	H63-2003-A	H63-2004-A	H63-2005-A

Accessories for Type 2						
	SLT 1 x 2	SLT 2 x 2	SLT 3 x 2	SLT 4 x 2	SLT 5 x 2	SLT 6 x 2
Collection trough insulation	H63-1020-A	H63-1021-A	H63-1022-A	H63-1023-A	H63-1024-A	H63-1025-A

Type 3		
Model	SLT 4 x 3	SLT 6 x 3
Dimensions L x W mm	4075 x 3075	6075 x 3075
Total height mm	2375	2375
Collection volume, L	2 x 1000	3 x 1000
Art. No., galvanized	H63-1007-A	H63-1009-A
Art. No., galvanized, outside lacquered	H63-2007-A	H63-2009-A

Accessories for Type 3		
	SLT 4 x 3	SLT 6 x 3
Collection trough insulation	H63-1027-A	H63-1029-A



Electric heating, 2 kW, Ex-proof



Electric switchbox (exterior)

Switchbox	
Article No.	H63-9007-A



For accessories such as forced ventilation, lamps and shelving see page 101 !

Electric heating, premounted in factory, including collision protection							
Heating ex-proof, T3	1,5 kW	2 kW	3 kW	Heating not ex-proof	1,5 kW	2 kW	3 kW
Frost-free storage*	1x2 / 2x2	3x2 / 4x2	6x2	Frost-free storage	1x2 / 2x2	3x2 / 4x2	6x2
for SLT-Type:		5x2 / 4x3	6x3	for SLT-Type:		5x2 / 4x3	6x3
Article No.	H63-9001-A	H63-9002-A	H63-9003-A	Article No.	H63-9004-A	H63-9005-A	H63-9006-A

* Requires collection trough insulation