


By using water protection storage halls a generously dimensioned storage facility for hazardous goods can be set up quickly at a favourable price. The standard roller door (W x H 2.6 x 2.5 m) permits convenient handling with all commercially available transport aids.

- ✎ Stable construction made from specially profiled and galvanized sheet steel; statics can be tested
- ✎ Max. roof loading 180 kg/m<sup>2</sup>
- ✎ Freely moving manual roller door as standard (W x H mm = 2600 x 2500)
- ✎ Side door (W x H mm = 1000 x 2200)
- ✎ Built-in floor safety elements made from 3 mm sheet steel with removable fire galvanized support grids
- ✎ Supplied dismantled with assembly instructions
- ✎ Wide range of accessories



Collection trough systems

Shelving systems for hazardous substances

Safety cabinets

Open-air storage systems / projects

Fire protection container systems

Gas cylinder storage systems

Safety containers, handling systems, ...



WS-LH 5 x 6, Article No. H62-1210-B, with optional shelving, drive-on ramp and additional outer lacquering



Equipped with shelving and skylight panel in roof (on request)



Equipped with shelving for use as small container store



Water protection storage hall, special version with thermal insulation



**If flammable liquids are to be stored then forced ventilation is required.**



See practical info on pages 60 and 94!

Collection trough systems

Shelving systems for hazardous substances

Safety cabinets

Open-air storage systems / projects

Fire protection container systems

Gas cylinder storage systems

Safety containers, handling systems, ...



Equipped with shelving for use as small container store



Skylight panel 2 x 2 m in roof, price on request

| Model                                    | WS-LH 5 x 6 | WS-LH 5 x 8 | WS-LH 5 x 10 |
|------------------------------------------|-------------|-------------|--------------|
| External dimensions L x W mm             | 5100 x 6100 | 5100 x 8100 | 5100 x 10100 |
| Total height mm                          | 3030        | 3030        | 3030         |
| Useful inner height mm                   | 2690        | 2690        | 2690         |
| Base area m <sup>2</sup>                 | 30          | 40          | 50           |
| Collection volume, L                     | 6 x 200     | 8 x 200     | 10 x 200     |
| Max. base trough load, kg/m <sup>2</sup> | 5000        | 5000        | 5000         |
| Article No., galvanized                  | H62-1210-B  | H62-1211-B  | H62-1212-B   |

| Accessories                                                           | Article No. |
|-----------------------------------------------------------------------|-------------|
| Shelf support, vertical                                               | H61-9020-B  |
| Shelf arm, horizontal, 500 mm                                         | H61-9002-B  |
| Grid-type shelf, W x D mm = 900 x 500 mm                              | H61-9003-B  |
| Grid-type shelf, W x D mm = 1900 x 500 mm                             | H61-9004-B  |
| Grid-type shelf, W x D mm = 2900 x 500 mm                             | H61-9005-B  |
| Ramp L x W x H mm = 1000 x 1000 x 80                                  | H61-9021-B  |
| Splash-protection panel, galvanized, height 500 mm, per running metre | H61-9022-B  |



**Further accessories such as skylight panels in the roof, anti-condensation coating, windows or electrical fittings such as lighting or forced ventilation available on request!**